



- Cast iron heat exchanger and stainless steel burners
- Integral fan for sidewall venting
- Six sizes available in natural or LP gas
- Limited lifetime warranty
- LWCO standard equipment
- Optional direct vent kit available (allows for direct connection of outside combustion air)
- Boiler easily field convertible to left side piping

See back side for piping configuration.

BALI 2[®] Gas-Fired Hot Water Boiler

Designed for reliability, efficiency and performance. For residential and small commercial applications with approved chimney.




INTEGRATED BOILER CONTROL

- Located inside the jacket and easily accessible from front of boiler.
- Temperature control, relay, and ignition functions in a single module.
- Includes additional circulator output for a second zone or an indirect water heater like the Mega-Stor II.

Quality
Value &
Service

BWF SERIES - BALI 2®

TECHNICAL SPECIFICATIONS



BWF Space Heating Ratings						AHRI CERTIFIED www.ahridirectory.org	# of Sections	'A' Width	Connection Size		Water Content	Approx. Shipping Weight	Optional Direct Vent Kit ⁽³⁾
Basic Boiler Model	Fuel	Input ⁽¹⁾	Heating Capacity	Net AHRI Rating, Water ⁽²⁾	AFUE				Gas	Vent			
		MBH	MBH	MBH	%								
BWF070BN	NAT. GAS	70	60	52	85.0	3	12-3/4	1/2	3	2	260	110019-03	
BWF105BN	NAT. GAS	105	90	78	85.0	4	15-1/2	1/2	3	3	310	110019-04	
BWF140BN	NAT. GAS	140	120	104	85.0	5	18-1/2	1/2	3	4	360	110019-05	
BWF175BN	NAT. GAS	175	150	130	85.0	6	21-1/2	1/2	3	5	415	110019-06	
BWF210BN	NAT. GAS	210	179	156	85.0	7	24-3/4	3/4	3	6	470	110019-07	
BWF245BN	NAT. GAS	245	208	181	84.0	8	27-3/4	3/4	4	7	525	110019-08	
BWF063BL	PROPANE	63	54	47	85.0	3	12-3/4	1/2	3	2	260	110019-03	
BWF094BL	PROPANE	94.5	81	70	85.0	4	15-1/2	1/2	3	3	310	110019-04	
BWF126BL	PROPANE	126	108	94	85.0	5	18-1/2	1/2	3	4	360	110019-05	
BWF157BL	PROPANE	157.5	135	117	85.0	6	21-1/2	1/2	3	5	415	110019-06	
BWF189BL	PROPANE	189	161	140	85.0	7	24-3/4	3/4	3	6	470	110019-07	
BWF220BL	PROPANE	220.5	187	163	84.0	8	27-3/4	3/4	4	7	525	110019-08	

⁽¹⁾ Input ratings can be used for elevations up to 2000 ft above sea level. Refer to Appendix B in the installation manual for elevations 2000 ft. or higher. ⁽²⁾ Net AHRI Water Ratings shown are based on a piping and pickup allowance of 1.15. Consult manufacturer before selecting boiler for installations having unusual piping and pickup requirements, such as intermittent system operation, extensive piping systems, etc. ⁽³⁾ Direct Vent kit is included with high altitude models.

All residential cast iron boiler models include a full one-year warranty. A limited lifetime warranty is provided for the heat exchanger. A 5-year and a 10-year extended warranty covering parts and labor are also available. Visit VelocityBoilerWorks.com or see your warranty for complete details.

ADDITIONAL FEATURES/BENEFITS

- Gas valve and all controls mounted inside the jacket
- Temperature/pressure gauge and drain valve included
- Reliable Honeywell controls
- Designed for installation on combustible floors



The Mega-Stor II® indirect water heater utilizes the energy created by your boiler to produce abundant hot water for your home. Mega-Stor II water heaters come in a variety of sizes from 26 to 119 gallons to meet a variety of residential and commercial needs. A Horizontal model is also available in 40 and 53 gallon sizes.

Specifications are subject to change

