



# ARUBA 5 Gas-Fired Hot Water Boiler

Designed for reliability, efficiency and performance. For residential and small commercial applications with approved chimney.




- Cast iron heat exchanger
- Boiler easily field convertible to left side piping
- Built-in rear draft diverter to fit low spaces
- Eight sizes from 38 to 280 MBH
- Limited lifetime warranty
- LWCO standard equipment

## INTEGRATED BOILER CONTROL

- Located inside the jacket and easily accessible from front of boiler.
- Temperature control, relay, and ignition functions in a single module.
- Includes additional circulator output for a second zone or an indirect water heater like the Mega-Stor II.

Quality  
Value &  
Service

# AWR SERIES - ARUBA 5 TECHNICAL SPECIFICATIONS



AWR SPACE HEATING RATINGS NATURAL AND LP GAS					NO. OF SECTIONS	DIMENSIONS (IN.)			SHIPPING WEIGHT (LBS.)
CROWN MODEL NUMBER	INPUT (MBH)	HEATING CAPACITY (MBH)	AHRI NET RATING WATER (MBH)	AFUE (%)		'A'	'B'	'C'	
AWR038B	38	32	28	84.0	2	9-3/4	31-1/2	4	234
AWR070B	70	59	51	84.0	3	12-7/8	31-1/2	4	284
AWR105B	105	88	77	84.0	4	15-3/8	31-1/2	5	334
AWR140B	140	117	102	84.0	5	18-1/2	31-1/2	6	384
AWR175B	175	146	127	84.0	6	21-1/2	31-3/4	7	434
AWR210B	210	176	153	84.0	7	24-5/8	33-1/2	7	484
AWR245B	245	205	178	84.0	8	27-5/8	33-1/2	8	533
AWR280B	280	234	203	84.0	9	30-3/4	33-1/2	8	583

- Altitudes above 2,000 ft. - ratings should be reduced at a rate of 4% for each 1,000 ft. above sea level (US only). AWR038B not suitable for use above 2,000ft.
- The AHRI Net Water Ratings are based on a piping and pickup allowance of 1.15.
- The manufacturer should be consulted before selecting a boiler for installations having unusual piping and pickup requirements, such as intermittent system operation, extensive piping systems, etc.

All residential cast iron boilers include a full one year warranty. A limited, lifetime warranty is provided for the cast iron heat exchanger. A 5-year and a 10-year extended warranty covering parts and labor are also available. Visit [VelocityBoilerWorks.com](http://VelocityBoilerWorks.com) for complete details.

### Additional Features/Benefits

- Available with natural or LP gas
- Designed for installation on combustible floors
- Stack Damper; Rollout Switch; Blocked Vent Switch; ASME Relief Valve (30psi) and Circulator
- Stainless steel burners



The Mega-Stor II® indirect water heater utilizes the energy created by your boiler to produce abundant hot water for your home. Mega-Stor II water heaters come in a variety of sizes from 30 to 119 gallons to meet a variety of residential and commercial needs. A Horizontal model is also available in 40 and 53 gallon sizes.

Specifications are subject to change without notice.

