
## **PHANTOM**<sup>®</sup>

## **New Accessories for the Phantom®**



**EZ Loop Low Loss Header** This ready-made primary/secondary piping solution allows contractors to complete all near-boiler loop plumbing connections with speed and accuracy, saving time and money while optimizing flow for perfect system performance.



Phantom® Combi-Kit Add domestic hot water capabilities directly to the Phantom® 150 and 180 with one easy step, precisely matching to the existing boiler connections. The kit includes mixing valve, plate heat exchanger and the EZ-Loop Low Loss Header.



**Base Pedestal** 

When a wall installation does not work, the Phantom<sup>®</sup> Floor Pedestal is the perfect accessory for a clean and attractive installation. The Base Pedestal includes adjustable feet for uneven floors and works great with the EZ-Loop Low Loss Header or Phantom<sup>®</sup> Combi-Kit.

\*Eligible for PGW rebate.

MODEL	MAX. INPUT (MBH)	MIN. INPUT (MBH)	HEATING CAPACITY (MBH)	AHRI NET RATING (MBH)	AFUE (%)	WATER VOLUME (GAL)	DIMENSIONS (D x W x H)	SUPPLY & RETURN CONN. SIZE (NPT)	GAS CONN. SIZE (NPT)	APPROX. NET WEIGHT (LBS)
PHNTM080	80	16	74	64	94.0*	0.36	17" x 16-5/8" x 29-1/16"	1"	1/2"	100
PHNTM100	100	20	92	80	93.3	0.44	17" x 16-5/8" x 29-1/16"	1"	1/2"	102
PHNTM120	120	24	112	97	<b>94.0</b> *	0.53	17" x 16-5/8" x 29-1/16"	1"	1/2"	105
PHNTM150	150	30	142	123	95.0*	0.79	21" x 16-5/8" x 29-1/16"	1"	1/2"	119
PHNTM180	180	36	170	148	94.0*	0.79	21" x 16-5/8" x 29-1/16"	1"	1/2"	119

## NOTES:

 De-rate required on some models installed above 2,000 ft., consult factory for details. For Canadian installations over 4,500 ft., consult authority having jurisdiction for guidance. PHNTM080 may not be installed using LP gas above 2,000 ft. PHNTM180 may not be installed using LP gas above 7,800 ft.
The Net Water Ratings are based on a piping and pickup allowance of 1.15.

The manufacturer should be consulted before selecting a boiler for installations having unusual piping and pickup requirements, such as intermittent system operation, extensive piping systems, etc.

A Refer to manual for system year length derates

Refer to manual for system vent length derates.

All Phantom<sup>®</sup> boiler models include a full twoyear parts warranty. A 12-year limited warranty is provided for the heat exchanger. A 5-year and a 10-year extended warranty covering parts and labor are also available. Visit CrownBoiler.com or see your warranty for complete details.



The Mega-Stor<sup>®</sup> indirect water heater utilizes the energy created by your boiler to produce abundant hot water for your home. Mega-Stor water heaters come in a variety of sizes from 26 to 119 gallons to meet a multitude of residential and commercial needs.

## **ADDITIONAL FEATURES/BENEFITS**

- Selectable domestic hot water priority
- Boiler, system, and domestic hot water pump outputs
- Field convertible to LP gas
- Fuse protection for pump and transformer



Specifications are subject to change without notice.

www.phantomboiler.com

www.crownboiler.com | Philadelphia PA