



Service

- Designed with the technician in mind!
 - Easy to remove front control panel allows access to key components.
 - Side jacket panels can also be removed for additional interior component access if needed.
 - Control provides easy to understand information in plain text.

Support

- Proudly designed and assembled in the USA
- Factory direct online technical support available



Durability

- Proven Stainless Steel Water Tube Heat Exchanger
- 5-year parts warranty
- 12-year heat exchanger warranty

Performance

- 95% AFUE
- 10:1 turndown saves energy by allowing the boiler to match energy use with either heat or domestic hot water requirements.
- Increase energy management by adding the Sage Zone panel with individual zone load match capability.
- Up to 180 MBH of heating capacity and 4.5 gallons per minute of hot water at a 70° rise (PHNTM180CB).

Flexibility

- 3 sizes to choose from 135 MBH, 150 MBH and 180 MBH.
- Innovative touchscreen control allows for customizing boiler for both space heating and domestic hot water requirements.
- Venting
 - Universal vent connection allows for use of CPVC/PVC, PP or SS for venting up to 135'.
 - Multiple vent options side wall, through the roof, split system and the use of a stainless flex liner when using an adjacent chimney as a chase.

Installation

- Internal boiler pump is provided and installed
- Low voltage terminal strip for ease of wiring
 - System pump
 - Outdoor temperature sensor

