

# PHANTOM II

## OneVent Kits

Simple, safe venting performance for multiple Phantom II boiler installations.



Gas, supply, and return piping are not included with OneVent kit and are shown for illustration purposes only

### SIMPLE

- Common venting for (up to) four Phantom II heat-only boilers, ensures consistency
- Pre-engineered kits (4" & 6" diameter), all components included
- Gasket seams, no gluing or curing time
- Comprehensive step-by-step instructions
- Starter kit connects two boilers, add another boiler, add an extension kit

### SAFE

- Built in non-return valves, no backflow
- Siphon traps provide complete condensate drainage
- Airtight seals at section joints

### VENTING PERFORMANCE

- Lengths up to 150' with minimal derate (low as 4-9%), maintains efficiency even in long runs
- Use PAT Connect (app & bluetooth connector) for fast commission and adjustment of venting parameters
- Field adjustable modulation settings for each boiler in system ensure optimum performance

Part Number	Description	Application
112851-01	OneVent 4" diameter starter kit	Connects two boilers
112849-01	OneVent 6" diameter starter kit	Connects two boilers
112850-01	OneVent 4" diameter extension kit	Adds one boiler
112852-01	OneVent 6" diameter extension kit	Adds one boiler

### NOTES

- For heating-only Phantom II boilers - **not compatible with combi models**
- Compatible with 120, 150, and 180 MBH sizes
- Boilers must be piped in the same heating system distribution loop - no individual water piping system per boiler
- For use in applications up to 10,100 ft. elevation



VelocityBoilerWorks.com | Philadelphia, PA

PHTMOV-3/26  
PN 981000