

PHANTOM II

OneVent Kits

Simple, safe venting performance for multiple Phantom II boiler installations.



Gas, supply, and return piping are not included with OneVent kit and are shown for illustration purposes only

SIMPLE

- Common venting for (up to) four Phantom II heat-only boilers, ensures consistency
- Pre-engineered kits (4" & 6" diameter), all components included
- Gasket seams, no gluing or curing time
- Comprehensive step-by-step instructions
- Starter kit connects two boilers, add another boiler, add an extension kit

SAFE

- Built in non-return valves, no backflow
- Siphon traps provide complete condensate drainage
- Airtight seals at section joints

VENTING PERFORMANCE

- Lengths up to 150' with minimal derate (low as 4-9%), maintains efficiency even in long runs
- Set-up via Boiler Connect (app & bluetooth connector) for fast commission and adjustment of venting parameters
- Field adjustable modulation settings for each boiler in system ensure optimum performance

Part Number	Description	Application
112851-01	OneVent 4" diameter starter kit	Connects two boilers
112849-01	OneVent 6" diameter starter kit	Connects two boilers
112850-01	OneVent 4" diameter extension kit	Adds one boiler
112852-01	OneVent 6" diameter extension kit	Adds one boiler

NOTES

- For heating-only Phantom II boilers - **not compatible with combi models**
- Compatible with 120, 150, and 180 MBH sizes
- Boilers must be piped in the same heating system distribution loop - no individual water piping system per boiler
- For use in applications up to 10,100 ft. elevation



VelocityBoilerWorks.com | Philadelphia, PA

PHTMOV-9/26
PN 981000